

PREMIUM STEEL POST SHORES / PREMIUM ACERO PARALES

Specification: 7'7.5"-13'8" (2.32M - 4.17M)

Outside Pipe Dia. / **Diametro exterior del tubo:** $\Phi 89\text{mm} \times 4\text{mm}$

Inner Pipe Dia. / **Diametro de la tubería en el interior:** $\Phi 76\text{mm} \times 4\text{mm}$

STORK®

Materials Technology

Stork Southwestern Laboratories

W/O. No.: MIC214-02-29-40334 -1

Report Date: February 29, 2008

Height	Maximum Load / Máximo		
	(kN)	(kgs)	(lbs)
3.05m (10'0")	196.62	20,049	44,200
3.20m (10'6")	189.25	19,297	42,543
3.35m (11'0")	174.50	17,821	39,228
3.51m (11'6")	152.38	15,538	34,255
3.66m (12'0")	159.76	16,290	35,913
3.81m (12'6")	145.01	14,786	32,598
3.96m (13'0")	142.55	14,536	32,045
4.11m (13'6")	137.63	14,034	30,940
4.27m (14'0")	137.63	14,034	30,940
4.42m (14'6")	108.14	11,027	24,310
4.57m (15'0")	88.48	9,022	19,890
4.72m (15'6")	90.93	9,263	20,442
4.88m (16'0")	86.01	8,770	19,335
5.03m (16'6")	88.48	9,022	19,890
5.18m (17'0")	93.39	9,523	20,995
5.33m (17'6")	85.72	8,741	19,270

All heights 14'0" and above include the addition of a 4' extension

Todas las alturas de 14 y arriba incluyen la adición de un 4' de extension



TESTING / PRUEBAS